

# LED Horizontal Wall Pack

- Aluminum rust-proof body
- Instant start electronic unit
- Suitable for wet location (IP65)
- 5-year limited warranty



## SPECIFICATIONS

Input Line Frequency \_\_\_\_\_ 60Hz  
 Lamp Life (Rated) \_\_\_\_\_ 50,000Hrs  
 Minimum Starting Temp \_\_\_\_\_ -20°C  
 Maximum Operating temp \_\_\_\_\_ 45°C  
 CRI \_\_\_\_\_ ≥80

## DIMENSIONS

LWP45FHZ850 \_\_\_\_\_ 9.75" x 18" x 8.75"  
 LWP65FHZ850 \_\_\_\_\_ 13.07" x 14.21" x 7.2"  
 LWP90FHZ850 \_\_\_\_\_ 13.07" x 14.21" x 7.2"  
 LWP135FHZ850 \_\_\_\_\_ 9.75" x 18" x 15.63"



WATTS	MODEL NO.	LUMENS	CCT	VOLTAGE	REPLACES
45	LWP45FHZ850	5,300	5000	120-277	150W MH
65	LWP65FHZ850	7,800	5000	120-277	250W MH
90	LWP90FHZ850	10,500	5000	120-277	320W MH
135	LWP135FHZ850	16,400	5000	120-277	400W MH

NOTES:

Manufactured by

