

# LED Architectural Flood w/Photo Control

- Standard with photo control
- Finned heat sinks shed water and debris
- Heavy durable aluminum housing with collimated reflector (NEMA 6x6/7x7 wattage dependent)
- Pictured with slip fitter (E1AFLA1), 1/2" BSPP elbow (E1AFLNPT) and yoke mount (E1AFLSVL) **all sold separately**
- Suitable for wet location
- Limited 5-year warranty



## SPECIFICATIONS

Input Line Frequency \_\_\_\_\_ 60Hz  
 Lamp Life (Rated) \_\_\_\_\_ 50,000Hrs  
 Minimum Starting Temp \_\_\_\_\_ -40°C  
 Maximum Operating temp \_\_\_\_\_ 40°C  
 CRI \_\_\_\_\_ 72  
 Power Factor \_\_\_\_\_ ≥0.95  
 THD \_\_\_\_\_ ≥15%

## DIMENSIONS

E1AFL50DL750 \_\_\_\_\_ 6.0" x 8.0" x 4.5"  
 E1AFL75DL750 \_\_\_\_\_ 7.5" x 10.0" x 5.5"  
 E1AFL100DL750 \_\_\_\_\_ 7.5" x 10.0" x 5.5"



WATTS	MODEL NO.	LUMENS	CCT	VOLTAGE	REPLACES
50	E1AFL50DL750	6,430	5000	120-277	100W MH
76	E1AFL75DL750	9,670	5000	120-277	175W MH
101	E1AFL100DL750	12,770	5000	120-277	250W MH
ACCESSORIES:	E1AFLA1				
	E1AFLNPT				
	E1AFLSVL				
NOTES:					

Manufactured by

**energetic**  
Smarter lighting