


LED Panel

- Instant-on LED
- Junction box for easy connection
- White framed edge
- Aircraft cable suspension kit (CLAC-KIT) sold separately
- Surface mount kit (CLFP14/CLFP22/CLFP24) sold separately
- Optional backup battery (CLBATBACKUP) sold separately - see page 93
- 5-year limited warranty

Project	Type
Catalog Number	
	

SPECIFICATIONS

Input Line Frequency _____ 60Hz
 Lamp Life (Rated) _____ 50,000Hrs
 Minimum Starting Temp _____ -20°C
 Maximum Operating temp _____ 40°C
 CRI _____ ≥80
 Power Factor _____ <0.90
 THD _____ 20%
 Dimmable _____ 10% 0-10V

DIMENSIONS

CL36P14DCW _____ 11.74" x 47.72" x 2.15"
 CL36P22DCW _____ 23.74" x 23.74" x 2.15"
 CL50P24DCW _____ 47.72" x 23.74" x 2.15"



WATTS	MODEL NO.	LUMENS	CCT	VOLTAGE	REPLACES
36	CL36P14DCW	4,000	4000	120-277	2/3 x 32W
36	CL36P22DCW	4,000	4000	120-277	2/3 x 32W
50	CL50P24DCW	5,500	4000	120-277	3/4 x 32W
ACCESSORIES:	CLAC-KIT				
	CLFP14				
	CLFP22				
	CLFP24				
	CLBATBACKUP				
NOTES:					

Manufactured by

