

- Die-cast aluminum housing
- Indoor/Outdoor
- Instant start electronic unit
- Suitable for wet locations
- 3-year limited warranty



## **SPECIFICATIONS**

| Input Line Frequency   | 60Hz       |
|------------------------|------------|
| Lamp Life (Rated)      | 25,000Hrs  |
| Minimum Starting Temp  | 20°C       |
| Maximum Operating temp | 40°C       |
| CRI                    | ≥90        |
| Dimmable               | Triac 120V |

## **DIMENSIONS**

| C147SQDISKNS  | 8" x 8" x 1"   |
|---------------|----------------|
| C2211SQDISKNS | 11" × 11" × 1" |





| WATTS  | MODEL NO.     | LUMENS | CCT  | VOLTAGE | REPLACES |
|--------|---------------|--------|------|---------|----------|
| 14     | C147SQDISKNS  | 720    | 3000 | 120     | 60W INC  |
| 22     | C2211SQDISKNS | 1320   | 3000 | 120     | 100W INC |
| NOTES: |               |        |      |         |          |
|        |               |        |      |         |          |
|        |               |        |      |         |          |
|        |               |        |      |         |          |
|        |               |        |      |         |          |
|        |               |        |      |         |          |
|        |               |        |      |         |          |
|        |               |        |      |         |          |

Manufactured by



