

# LED Arch. Emergency w/Photocell

- Die-cast aluminum housing available in black, dark bronze and white powder-coated finish
- Can be used as Normally-On or Normally-Off as well as on a switched circuit
- Integrated photocell standard
- Self-diagnosing, minimum 90 minute emergency
- Push-to-test switch and charge indicator
- Ni-Cad premium battery and high-lumen LEDs
- 5-year limited warranty

<b>Project</b>	<b>Type</b>
<b>Catalog Number</b>	
	

## SPECIFICATIONS

Input Line Frequency \_\_\_\_\_ 60Hz  
 Lamp Life (Rated) \_\_\_\_\_ 50,000Hrs  
 Minimum Starting Temp \_\_\_\_\_ 0°C  
 Maximum Operating temp \_\_\_\_\_ 50°C

## DIMENSIONS

DBELACEMHLXXPC \_\_\_\_\_ 6.56" x 10.5" x 3.63



WATTS	MODEL NO.	LUMENS	CCT	VOLTAGE	REPLACES
9	DBELACEMHLBPC	350-1,286	5,700	120-277	50W MH
9	DBELACEMHLBZPC	350-1,286	5,700	120-277	50W MH
9	DBELACEMHLWPC	350-1,286	5,700	120-277	50W MH

NOTES:

Manufactured by

