


LED Strip

- Suitable for surface or suspension mounting
- Steel body
- Post painted soft edges
- Easy-fit polycarbonate lens
- Damp location rated
- 5-year limited warranty

Project	Type
Catalog Number	
	

SPECIFICATIONS

Input Line Frequency _____ 60Hz
 Lamp Life (Rated) _____ 50,000Hrs
 Minimum Starting Temp _____ -20°C
 Maximum Operating temp _____ 40°C
 CRI _____ ≥80
 Dimmable _____ 0-10V

DIMENSIONS

ST4824SLED _____ 47.5" x 3.63" x 3.25"
 ST48XXLLED _____ 47.5" x 4.44" x 3.56"
 ST96XXLLED _____ 96.0" x 4.44" x 3.56"



WATTS	MODEL NO.	LUMENS	CCT	VOLTAGE	REPLACES
24	ST4824SLED840	2,650	4000	120-277	2 x 25W
24	ST4824SLED850	2,650	5000	120-277	2 x 25W
40	ST4840LLED840	4,400	4000	120-277	2 x 32W
40	ST4840LLED850	4,400	5000	120-277	2 x 32W
63	ST9660LLED840	7,100	4000	120-277	4 x 32W
63	ST9660LLED850	7,100	5000	120-277	4 x 32W
85	ST9685LLED840	9,000	4000	120-277	4 x 54W
85	ST9685LLED850	9,000	5000	120-277	4 x 54W
NOTES:					

Manufactured by

