


# LED Linear High Bay

- Includes V-hooks and 4' chain
- Clean powder-coated steel housing
- Driver and arrays isolated for heat control
- 1/2" knockouts at both ends
- Suitable for damp location use
- 5-year limited warranty

<b>Project</b>	<b>Type</b>
<b>Catalog Number</b>	
	

## SPECIFICATIONS

Input Line Frequency \_\_\_\_\_ 60Hz  
 Lamp Life (Rated) \_\_\_\_\_ 50,000Hrs  
 Minimum Starting Temp \_\_\_\_\_ -40°C  
 Maximum Operating temp \_\_\_\_\_ 50°C  
 CRI \_\_\_\_\_ 82  
 Power Factor \_\_\_\_\_ 0.90  
 THD \_\_\_\_\_ .10  
 Dimmable \_\_\_\_\_ 0-10V

## DIMENSIONS

E2HBDXXX850 \_\_\_\_\_ 24.5" x 15.0" x 2.5"



WATTS	MODEL NO.	LUMENS	CCT	VOLTAGE	REPLACES
65	E2HBD65850	8,450	5000	120-277	150W MH
110	E2HBD110850	13,755	5000	120-277	250W MH
165	E2HBD165850	21,222	5000	120-277	600W MH

NOTES:

Manufactured by

**energetic**  
Smarter lighting