

LED Horizontal Color-Select Wall Pack w/ photo control

- Switchable CCT (3/4/5K)
- Photocell included with Quick Disconnect
- Aluminum rust-proof body with bronze powder coat
- Polycarbonate lens with UV stabilization
- Suitable for wet location (IP65)
- 5-year limited warranty



SPECIFICATIONS

Input Line Frequency _____ 50/60Hz
 Lamp Life (Rated) _____ 50,000Hrs
 Minimum Starting Temp _____ -40°C
 Maximum Operating temp _____ 45°C
 CRI _____ ≥80
 Dimmable _____ 10% 0-10V

DIMENSIONS

LWP40FHZCCT _____ 8.27" x 10.25" x 7.6"
 LWP60FHZCCT _____ 8.27" x 10.25" x 7.6"
 LWP80FHZCCT _____ 9.33" x 14.37" x 7.36"
 LWP120FHZCCT _____ 9.33" x 14.37" x 7.36"



WATTS	MODEL NO.	LUMENS	CCT	VOLTAGE	REPLACES
40	LWP40FHZCCT	4,800	3/4/5K	120-277	100W MH
60	LWP60FHZCCT	7,200	3/4/5K	120-277	150W MH
80	LWP80FHZCCT	9,600	3/4/5K	120-277	250W MH
120	LWP120FHZCCT	14,400	3/4/5K	120-277	320W MH

NOTES:

Manufactured by

