


# 480V LED Premium High Bay

- Non-corrosive powder coated steel body
- Standard with polycarbonate diffuser
- Suspension hardware can transfer directly over for ease of installation
- Suitable for damp location
- 5-year limited warranty

Project	Type
Catalog Number	
	

## SPECIFICATIONS

Input Line Frequency \_\_\_\_\_ 60Hz  
 Lamp Life (Rated) \_\_\_\_\_ 50,000Hrs  
 Minimum Starting Temp \_\_\_\_\_ -20°C  
 Maximum Operating temp \_\_\_\_\_ 50°C  
 CRI \_\_\_\_\_ 82  
 Power Factor \_\_\_\_\_ 0.90  
 THD \_\_\_\_\_ 10%  
 Dimmable \_\_\_\_\_ 10% 0-10V

## DIMENSIONS

E2HBDH165 \_\_\_\_\_ 12.6" x 23.9" x 3.7"  
 E2HBDH225 \_\_\_\_\_ 17.4" x 23.9" x 3.7"  
 E2HBDH325 \_\_\_\_\_ 12.6" x 45.9" x 3.7"



WATTS	MODEL NO.	LUMENS	CCT	VOLTAGE	REPLACES
165	E2HBDH165850	21,222	5000	<b>347-480</b>	400W MH
225	E2HBDH225850	29,213	5000	<b>347-480</b>	750W MH
325	E2HBDH325850	42,051	5000	<b>347-480</b>	1000W MH

NOTES:

Manufactured by

**energetic**  
Smarter lighting