


LED Premium High Bay

- Built in heavy duty Y-hangers with 3' chain
- Standard with frosted white polycarbonate lens
- Non-corrosive powder coated steel body
- 5-year limited warranty

Project	Type
Catalog Number	
	

SPECIFICATIONS

Input Line Frequency _____ 60Hz
 Lamp Life (Rated) _____ 50,000Hrs
 Minimum Starting Temp _____ -40°C
 Maximum Operating temp _____ 40°C
 CRI _____ ≥80
 Power Factor _____ <0.90
 THD _____ 10%
 Dimmable _____ 10% 0-10V

DIMENSIONS

HL1XXI850 _____ 25.0" x 19.69" x 1.83"
 HL220I850 _____ 32.0" x 19.69" x 1.83"
 HL300I850 _____ 35.43" x 15.16" x 1.89"



WATTS	MODEL NO.	LUMENS	CCT	VOLTAGE	REPLACES
110	HL110I850	14,500	5000	120-277	250W MH
135	HL135I850	19,000	5000	120-277	400W MH
165	HL165I850	23,000	5000	120-277	600W MH
220	HL220I850	29,800	5000	120-277	750W MH
300	HL300I850	41,150	5000	120-277	1000W HPS

NOTES:

Manufactured by

